

# Tiger Neo N-type 54HL4R-(V) 425-445 Watt MONO-FACIAL MODULE


## N-Type

IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018  
Occupational health and safety management systems  
(Made in China)



## Key Features



### SMBB Technology

Better light trapping and current collection to improve module power output and reliability.




### Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).



## LINEAR PERFORMANCE WARRANTY





**25\*** Year Product Warranty

**30** Year Linear Power Warranty

**0.40%** Annual Degradation Over 30 years

\*The product warranty is only applicable in Australia

## Engineering Drawings




\*This tolerance range applies only to the four-angle distance of the module as indicated above.

## Packaging Configuration

( Two pallets = One stack )

36pcs/pallets, 72pcs/stack, 936pcs/ 40'HQ Container

## Electrical Performance & Temperature Dependence



## Mechanical Characteristics

Cell Type N type Mono-crystalline

No. of cells 108 (2×54)

Dimensions 1762×1134×30mm (69.36×44.65×1.18 inch)

Weight 22 kg (48.50 lbs)

Front Glass 3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass

Frame Anodized Aluminium Alloy

Junction Box IP68 Rated

Output Cables TUV 1×4.0mm<sup>2</sup>  
(+): 400mm, (-): 200mm or Customized Length

Connector 1000V: Staubli MC4, JK03M/1B, JK03M2/1B, Jinko PV material  
Type 1500V: Staubli MC4-EVO2, JK03M/2B, JK03M2/2B, Jinko PV material

Fire Class Class C

## SPECIFICATIONS

Module Type	JKM425N-54HL4R		JKM430N-54HL4R		JKM435N-54HL4R		JKM440N-54HL4R		JKM445N-54HL4R	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	425Wp	320Wp	430Wp	323Wp	435Wp	327Wp	440Wp	331Wp	445Wp	335Wp
Maximum Power Voltage (Vmp)	32.18V	29.99V	32.38V	30.10V	32.59V	30.33V	32.81V	30.56V	33.02V	30.76V
Maximum Power Current (Imp)	13.21A	10.67A	13.28A	10.73A	13.35A	10.78A	13.41A	10.83A	13.48A	10.89A
Open-circuit Voltage (Voc)	38.75V	36.81V	38.95V	37.00V	39.16V	37.20V	39.38V	37.41V	39.59V	37.61V
Short-circuit Current (Isc)	13.66A	11.03A	13.73A	11.09A	13.80A	11.14A	13.86A	11.19A	13.93A	11.25A
Module Efficiency STC (%)	21.27%		21.52%		21.77%		22.02%		22.27%	
Operating Temperature (°C)	-40°C~+85°C									
Maximum system voltage	1000/1500VDC (IEC) with -V=1500V, without -V=1000V									
Maximum series fuse rating	25A									
Power measurement tolerance	±3%									
Temperature coefficients of Pmax	-0.29%/°C									
Temperature coefficients of Voc	-0.25%/°C									
Temperature coefficients of Isc	0.045%/°C									
Nominal operating cell temperature (NOCT)	45±2°C									

\*STC: Irradiance 1000W/m<sup>2</sup> Cell Temperature 25°C

AM=1.5

NOCT: Irradiance 800W/m<sup>2</sup> Ambient Temperature 20°C

AM=1.5

Wind Speed 1m/s